



Mobile printer K329

Newly design / 2-3 inch / Portable / Class-leading

- Great looking design.
- Bluetooth 4.2 Low Energy and passive NFC tags for quick pair.
- Dual capabilities: Receipts & Labels
- Long-lasting battery and intelligent power consumption control for long work shifts.
- Compatible with multiple programming languages, reducing re-development.
- Visual editing apps, design at view, easy print.



Retails



Transportation



Manufacturing



Traffic Enforcement

K329 Mobile Printer

Specifications

UROVO



Printer Specifications

Print Method: Direct Thermal
Resolution: 203dpi/8dots/mm
Maximum Print Width: 72mm
Maximum Print Speed: up to 120mm/s



Memory

RAM: 8MB
FLASH: 16MB



Font

Bitmap fonts: ASCII(8*16, 12*24, 16*32),
GBK(16*16, 24*24, 32*32) BIG 5(16*16, 32*32)
TTF fonts can be downloaded



Barcode symbologies

1D: Code 39, Code 128, ITF, EAN-8,
EAN-13 etc.
2D: QR Code, PDF417, Data Matrix, etc



Media Sensors

Gap, Blackmark,
Media out, Media cover open, etc



Buttons & Display

Power button,
Feed/Configure button;
LED Display



Media Characteristics

Media width: 42~80mm
Maximum Roll Outside Diameter: 50mm
Media thickness: 0.06~0.16mm
Media types: Direct Thermal



Battery

Li-Ion 7.4V 2500mAh



Communications

USB Type-C
Bluetooth 4.2 + 2.1
2.4GHz & 5GHz WIFI (optional)



Programming Languages

TSPL, CPCL, ESC/POS, etc.



Physical Characteristics

Dimension: 118mm*105mm*62mm
Weight: 450g



Environmental

Operating Temperature: 0~50°C (32~122°F)
Storage Temperature: -20~60°C (-4~140°F)
Operating Humidity:
20%~85% non-condensing
Drop Spec: 1.5m tested over operating
temp range