

# OPN-2500

## Laser engine

The OPN-2500 allows real-time barcode scanning into any Bluetooth device, as well as scanning in batch mode. It is extremely small and lightweight, and it comes at an affordable price point that enables any business to integrate barcode scanning into their mobile applications.



## Highlights

- Price point makes real-time barcode scanning with any Bluetooth host device affordable
- HID (Human Interface Device), DFU (Device firmware update), UART (Serial port emulation), BAS (Battery service), OptiConnect service
- Bluetooth 5.4 Low Energy
- Ready-to-go out of the box, just pair it with your Bluetooth device or connect with USB
- High speed 100 scans/second laser barcode scanner
- The internal flash memory safely stores your data even without active connection
- 3-in-1 default application (Bluetooth, OPN2001 and Batch application)
- Fully configurable and customizable using OptiConnect, OptiConfigure and the OPN

- Companion application. Integrate with your own applications using our free SDKs
- By supporting a wide range of Bluetooth and USB interfaces and configurable batch capabilities, it integrates seamlessly with almost any existing or new barcode application
- When connected to the optional finger trigger, the scanner transforms into a ring scanner, perfect for hands-free operations and streamlined workflows.
- Audible and visible feedback
- USB-C charging/communications port. It supports USB-HID (keyboard), USB-COM (serial port profiles: USB-CDC and USB-VCP) and USB-MSD (hard disk)
- High capacity Lithium-Ion battery
- Two year warranty

# OPN-2500

## Product Specifications



### Operation

**CPU:** 32-bit  
**O/S:** Proprietary  
**Software:** 3-in-1 default applications (Bluetooth, OPN2001, and Batch application)  
**RTC:** Supports year, month, day, hour, minute, second (leap year supported)

### Memory

**Flashrom:** 1 MB  
**SRAM:** 256 kB  
**External Flashrom:** 2 MB

### Operating indicators

**Visual:** 2 LED (RGB)  
**Non-visual:** buzzer

### Operating keys

**Entry options:** 2 keys (1 scan button, 1 function key)

### Communication

**USB:** USB-C, USB-VCP, USB-CDC, USB-HID, USB-MSD  
**Bluetooth:** Ver. 5.4, HID (Human Interface Device), DFU (Device firmware update), SPP (Serial port emulation), BAS (Battery service), OptiConnect service

### Power

**Rechargeable battery:** lithium-Ion Polymer 3.7V 250 mAh  
**Operating time (batch):** 12,500 scans (1 scan / 5 sec)  
**Operating time (Batch, idle):** >6 months  
**Operating time (Bluetooth):** 12,000 scans (1 scan / 5 seconds)  
**Operating time (Bluetooth, idle):** >1 month  
**Data retention time:** Indefinite  
**Charge method:** Enclosed USB-C cable

### Barcode scanner optics

**Light source:** 650 nm visible laser diode  
**Scan method:** Vibrating mirror  
**Scan rate:** Up to 100 scans / second  
**Reading pitch angle:**  $\pm 35^\circ$   
**Reading skew angle:**  $-50^\circ$  to  $-8^\circ$ ,  $+8^\circ$  to  $+50^\circ$   
**Reading tilt angle:**  $\pm 20^\circ$

**Curvature:** R>15 (EAN 8), R>20 (EAN 13)

**Min. resolution at pcs 0.9:** 0.127 mm / 5 mil

**Min. PCS value:** 0.2

**Depth of field:**

70 - 550 mm (1.00 mm) / 2.76 - 21.65 in (39 mil)

50 - 380 mm (0.5 mm) / 1.97 - 14.96 in (20 mil)

50 - 230 mm (0.25 mm) / 1.97 - 9.06 in (10 mil)

50 - 130 mm (0.15 mm) / 1.97 - 5.12 in (6 mil)

60 - 110 mm (0.127 mm) / 2.36 - 4.33 in (5 mil)

### Supported symbologies

**Barcode (1D):** JAN/UPC/EAN incl. add on, Codabar / nW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2 of 5, ISBN-ISMN-ISSN, Matrix 2 of 5, MSI/Plessey-UK/Plessey, S-Code, Telepen, Tri-Optic

**Postal code:** Chinese Post, Korean Postal Authority code

### Durability

**Temperature in operation:** 0 to 40 °C / 32 to 104 °F

**Temperature in storage:** -20 to 60 °C / -4 to 140 °F

**Humidity in operation:** 20% to 85% (no frost, non-condensing)

**Humidity in storage:** 20% to 85% (no frost, non-condensing)

**Ambient light immunity:** Incandescent 4,000 lx max, Fluorescent 4,000 lx max, direct sun 80,000 lx

**Max drop test:** 1.5 m / 5 ft drop onto concrete surface

**Vibration test:** 10 - 100Hz with 2G for 30 min

**Protection rate:** IP42

### Physical

**Dimensions (W x H x D):** 32 x 62 x 16 mm / 1.26 x 2.44 x 0.63 in

**Weight body:** Ca. 29 g / 1 oz (incl. battery)

**Case:** ABS, Black

### Regulatory & safety

**Product compliance:** CE, FCC, RoHS, IEC 60825-1 Class 2, FDA CDRH Class II

### Items

**Enclosed:** USB-C cable, Neck strap

**Sold separately:** Silicon cover, Finger trigger